



FOR MS21340 NUTS EXTERNAL KEYING

PART NUMBER	A +/- .005	B +/- .015	C +/- .005	D + .005-.030	NUT SIZE	WEIGHT LBS.
RL2-E121	0.255	0.636	0.325	0.438	1/4"	0.001
RL2-F121	0.320	0.680	0.325	0.500	5/16	0.001
RL2-G121	0.380	0.735	0.345	0.560	3/8"	0.001
RL2-H121	0.471	0.826	0.392	0.625	15/32"	0.001
RL2-J121	0.441	0.826	0.392	0.625	7/16"	0.001
RL2-K121	0.505	0.826	0.408	0.625	1/2"	0.001
RL2-M121	0.630	0.993	0.470	0.812	5/8"	0.001
RL2-N121	0.755	1.112	0.528	0.938	3/4"	0.002
RL2-R121	1.010	1.481	0.705	1.312	1.0"	0.003

BASE MATERIAL: STAINLESS STEEL 17-7, ROCKWELL HARDNESS Rc 43 min. FINISH OPTIONS BELOW

FINISH	SUFFIX	SPECIFICATION	NO SUFFIX MEANS NO FINISH	
ZINC	-Z	QQ-Z-325, CLASS2, TYPE II	SUFFIX IS NOTED ON PAPER-WORK ONLY NOT ON PART	
ELECTROLESS NICKEL	-E	MIL-C-26074, CLASS1, GRADE A		
SAINT TECHNOLOGIES, INC 10 NORTH LOCUST BOX 66 SHANNON, IL 61078 PHONE: 515.864.3035 FAX: 815.864.3134 CAGE 60198		TITLE: REALLOCK™, FOR MS-21340 NUTS WITH EXTERNAL KEYING	CHART NUMBER	
			2001	
			REV. E ECO S00068	04/09/2010