



## FOR MS21340 NUTS INTERNAL & EXTERNAL KEYING

PART NUMBER	A +/- .005	B +/- .005	C +.005 -.030	D +/- .005	E +/- .005	NUT SIZE	WEIGHT LBS.
RL2-G131	.0380	.735	.346	.345	0.560	3/8"	0.001
RL2-H131	0.471	0.826	0.437	0.392	0.625	15/32"	0.001
RL2-J131	0.441	0.826	0.407	0.392	0.625	7/16"	0.001
RL2-K131	0.505	0.826	0.471	0.408	0.625	1/2"	0.001
RL2-M131	0.630	0.993	0.596	0.470	0.812	5/8"	0.001
RL2-N131	0.755	1.112	0.717	0.528	0.938	3/4"	0.002
RL2-R131	1.010	1.481	0.958	0.705	1.312	1.0"	0.003

BASE MATERIAL: STAINLESS STEEL 17-7, ROCKWELL HARDNESS Rc 43 min. FINISH OPTIONS BELOW			
FINISH	SUFFIX	SPECIFICATION	NO SUFFIX MEANS NO FINISH
ZINC	-Z	QQ-Z-325, CLASS2, TYPE II	SUFFIX IS NOTED ON PAPER-WORK ONLY NOT ON PART
ELECTROLESS NICKEL	-E	MIL-C-26074, CLASS 1, GRADE A	
<b>SAINT TECHNOLOGIES, INC</b> 10 NORTH LOCUST BOX 66 SHANNON, IL 61078 PHONE: 515.864.3035 FAX: 815.864.3134 CAGE 60198		TITLE: REALLOCK tm, FOR MS-21340 NUTS WITH INTERNAL & EXTERNAL KEYING	<b>CHART NUMBER</b>
			2002
			REV. D ECO S00063

THIS DRAWING AND INFORMATION HEREIN IS THE EXCLUSIVE PROPERTY OF SAINT TECHNOLOGIES, INC. AND UNAUTHORIZED USE OR REPRODUCTION THEREOF IS PROHIBITED.