




FOR D38999/24 CONNECTORS TAB "D" SLOT KEYING

PART NUMBER	A +/- .005	B +/- .005	C +/- .005	D	SHELL SIZE	WEIGHT LBS.
RL9-N009	0.674	1.12	0.654	0.859-0.945	9	0.007
RL9-N002	0.792	1.24	0.756	0.984-1.063	11	0.003
RL9-R002	0.989	1.43	0.943	1.172-1.260	13	0.003
RL9-S001	1.107	1.59	1.067	1.296-1.417	15	0.004
RL9-T001	1.265	1.63	1.192	1.422-1.457	17	0.003
RL9-Z001	1.383	1.79	1.317	1.545-1.614	19	0.004
RL9-Z002	1.501	1.98	1.443	1.672-1.811	21	0.005
RL9-Z003	1.619	2.14	1.567	1.796-1.969	23	0.006
RL9-Z004	1.737	2.19	1.693	1.939-2.017	25	0.005

BASE MATERIAL: STAINLESS STEEL 17-7, Rockwell Hardness Rc 43 min. Finish Options listed below.

FINISH	SUFFIX	STC SPECIFICATION
ZINC	-Z	QQ-Z-325, CLASS 2, TYPE II
ELECTROLESS NICKEL	-E	MIL-C-26074, CLASS 1, GRADE A

Saint Technologies, Inc. 10 North Locust P.O. Box 66 Shannon, IL 61078 Phone: 815.864.3035 Fax: 815.864.3134 CAGE 60198	TITLE: REALLOCK™, FOR D38999/24 CONNECTORS & TAB "D" SLOT KEYING	CHART NUMBER
		2007
		REV G 03/14/2012 ECO S083